

TYPICAL PULL TYPE SPREADER CONFIGURATIONS

Hopper Length (ft)	Hopper Profile	Litter Struck Capacity (tons)	Axle System	Tires & Wheels	Recommended Options for Litter Only						Recommended Options for Litter & Lime								
					88k Chain	GR Valve	Poly Floor	Extra Gear Case	Ladder	Hopper Extension	88k Chain	GR Valve	Poly	Extra Gear	3rd Chain	Ladder	Extension	Bars EOL	Inverted V
16	S	6.4	7T torsion	12.5L x 15 6 bolt							X							X	X
18	S	7.2	9T torsion	16.5 x 16.1 8 bolt	X	X					X	X						X	X
20	S	8.0	9T torsion	16.5 x 16.1 8 bolt	X	X					X	X						X	X
20	SE6	9.3	10T walk beam	16.5 x 16.1 8 bolt	X	X				X	X	X				X	X	X	X
24	S	9.6	10T walk beam	16.5 x 16.1 8 bolt	X	X	X				X	X	X					X	X
24	HE6	11.8	14T walk beam	21.5 x 16.1 10 bolt	X	X	X			X	X	X	X			X	X	X	X
26	HE10	15.8	20T walk beam	710/60-30.5 10 bolt	X	X	X	X		X	X	X	X	X	X	X	X	X	X

Struck capacity based on 40lb / cu. ft. material